



NewtComm NC-50D-SH

Subsea Through Water Communications

Features:

- Selectable TX power: 50W, 25W, 5W
- Dual Frequency: 8kHz (NATO) & 25kHz
- Range: +10km @ 8kHz, 7.5km @ 25kHz
- Efficient output amplifier
- High gain, very low noise receiver
- Advanced noise filtering
- Serial port for modem functionality
- Compact and rugged
- Wide input voltage range
- Remote interface panel



Supplied and Supported By:



Applications:

- Primary comms for manned submersibles
- Backup comms for chambers, diving bells

The NewtComm NC-50D-SH is an advanced through water communication system. It provides a robust communications channel through the most challenging under water environments. Built with an advanced digital signal processor the NewtComm delivers powerful, clear and energy efficient communications. The NewtComm offers best-in-class transmission range, phone size and energy efficiency. The NC-50D-SH is the subsea hyperbaric version of the NC-50D. The comms unit is designed for direct integration into chambers with the power electronics enclosed outside the hull. It can communicate with other phones that utilize the same frequency. A single enclosure option that incorporates the power electronics in the control panel is also available. The NC50 series is standard equipment in the Nuytco DeepWorker submersible and Exosuit ADS.

The standard frequencies for the NewtComm NC-50D-SH are 8.087kHz and 25.00kHz, commonly called 10k and 27k. Modulation is upper single side band with a voice channel bandwidth of 6kHz (other frequencies available upon request). The phone with matched 8kHz and 25kHz transducers produces over 50 Watts rms transmit power. The phone has an open water range of over 10km @ 8kHz. Three selectable TX power levels allow for use in different ranges and operating environments. Voice pre-processing ensures a consistent TX signal that utilizes the full power of the phone.

The phone features extremely low noise receiver circuitry, capable of picking up the faintest signals. The receiver has selectable auto and manual gain control with range of 102dB. Advanced receiver filtering and squelch controls help reject unwanted noise from the voice channel. The phone unit has an integrated waterproof speaker rated for 10W.

The NC-50D-SH power amplifier and remote interface are built in waterproof enclosures suitable for use humid submarine conditions. The phone is compact and light weight, making it ideal for submersible vehicles.

Nuytco Research Ltd

216 East Esplanade, North Vancouver
B.C. V7L 1A3 Canada

Phone: 604 980 6262
Email: nrl@nuytco.com
Web: www.nuytco.com



NewtComm NC-50D-SH

Subsea Through Water Communications

Specifications

General:

- Advanced Digital Signal Processor
- Selectable TX Power
- 50W, 25W, 5W RMS
- 8kHz (NATO) & 25kHz USB Modulation
- Waterproof case
- Rugged connections
- Palm mic / Headset capable
- Line outs for TX and RX audio
- RS422/485 port for modem functionality

Open Water Range:

- Low Power (5W): 3.5km @ 25kHz
- Med Power (25W): 5km @ 25kHz
- High Power (50W): 7.5km @ 25kHz

Transmitter:

- Selectable TX Power
- 50W, 25W, 5W RMS TX Power
- Power efficient Class D Transmitter
- Voice envelope processing for powerful and consistent TX signal
- Matched transducer for maximum power transfer

Receiver:

- Very low noise receiver circuitry
- Automatic / Manual Gain Control with wide dynamic range of 102 dB
- Selectable voice channel bandwidth 6 – 3kHz
- Advanced 16 band Noise Reduction filter
- Squelch control
- Low RX power consumption 0.75W
- 10W speaker output

Transducer:

- NewtComm NC-XDR-27K
- NewtComm NC-XDR-10K
- MCBH2MSS Connector
- Rugged SS base
- #10-24 threaded mounting holes
- Air Weight: 0.47 kg, 1.1 lbs
- Water Weight: 0.31 kg, 0.7 lbs

Input Power:

- Wide range: 10-36 VDC
- Current: 9A peak @ 12VDC

Power Amp Enclosure:

- Rugged, waterproof diecast aluminum enclosure
- (L x W x H): 203 x 102 x 104 mm
- (L x W x H): 8.0" x 4.0" x 4.13"
- 1.4 kg, 3.1 lbs

Interface Panel:

- Rugged, waterproof diecast aluminum enclosure
- Speaker: 4 Ohm, 10W rms
- (L x W x H): 240x160x100 mm
- (L x W x H): 9.5" x 6.3" x 4.0"
- 2.5 kg, 5.5 lbs

All specifications subject to change without notice.

Nuytco Research Ltd

216 East Esplanade, North Vancouver
B.C. V7L 1A3 Canada

Phone: 604 980 6262
Email: nrl@nuytco.com
Web: www.nuytco.com